



BIRO Circle surface luminaire 1.000

Artikel-Nr. 13682163



1.0 m	3.213.0	4614.6
2.0 m	6.416.0	1153.6
3.0 m	9.618.9	512.7
4.0 m	12.811.9	288.4
5.0 m	16.014.9	184.6
Ø (m)	E0(0°) [lx]	

BIRO Circle surface luminaire 1.000, silver, round. Surface mounting, Ceiling-mounted. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP40, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 125W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 13.925lm, Light colour : White, Beam angle: 116°, With control gear: Yes. This luminaire contains incorporated and non-exchangeable LED light sources

Artikel-Nr.	13682163
Stand:	18.06.2021 16:28

Type of dimming	on/off
Colour	Silver
Colour of light	3000 K
System efficiency	111 lm/W
Luminous flux	13,925 lm
Material cover	Plastic, opal
Rated life time L80/B50 at 25 °C	50000 h
Rated life time L70/B50 at 25 °C	50000 h
System output	125 W
Colour rendering	CRI > 80
McAdam-Step	McAdam-Step 3
Beam angle	116 °

Amount of light sources / fittings	1 Qty
Outer diameter	1000 mm
Height	100 mm
Colour rendering	CRI > 80
Material	Aluminium / Steel / Plastic
Voltage	230V AC 50Hz
Lamp	LED
Light output	Direct
Shipping	Incl. converter for connection to the 230-V mains voltage
Degree of protection	IP40
Protection class	I
Voltage type	AC