


BIRO Circle surface luminaire 450
Artikel-Nr. 13695163



BIRO Circle surface luminaire 450, silver, round. Surface mounting, Ceiling-mounted. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP40, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 25W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.450lm, Light colour : White, Beam angle: 120°, With control gear: Yes. This luminaire contains incorporated and non-exchangeable LED light sources

Artikel-Nr.	13695163
Stand:	18.06.2021 17:49

Type of dimming	DALI	Amount of light sources / fittings	1 Qty
Colour	Silver	Outer diameter	450 mm
Colour of light	3000 K	Height	100 mm
System efficiency	98 lm/W	Colour rendering	CRI > 80
Luminous flux	2,450 lm	Material	Aluminium / Steel / Plastic
Material cover	Plastic, opal	Voltage	230V AC 50Hz
Rated life time L80/B50 at 25 °C	50000 h	Lamp	LED
Rated life time L70/B50 at 25 °C	50000 h	Light output	Direct
System output	25 W	Shipping	Incl. converter for connection to the 230-V mains voltage
Colour rendering	CRI > 80	Degree of protection	IP40
McAdam-Step	McAdam-Step 3	Protection class	I
Beam angle	120 °	Voltage type	AC