



BIRO Circle pendant surface luminaire 1.200, direct

Artikel-Nr. 13613163



Ø (m)	E0(0°) [lx]
1.0 m	6511.8
2.0 m	1627.9
3.0 m	723.5
4.0 m	407.0
5.0 m	260.5

BIRO Circle pendant surface luminaire 1.200, direct, silver, round. Suspended, Ceiling-mounted. Mounting method: Suspended, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP40, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 175W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 19.650lm, Light colour : White, Beam angle: 116°, With control gear: Yes. This luminaire contains incorporated and non-exchangeable LED light sources

Artikel-Nr.	13613163
Stand:	19.06.2021 00:38

Type of dimming	DALI
Colour	Silver
Colour of light	3000 K
System efficiency	112 lm/W
Luminous flux	19,650 lm
Material cover	Plastic, opal
Rated life time L80/B50 at 25 °C	50000 h
Rated life time L70/B50 at 25 °C	50000 h
System output	175 W
Colour rendering	CRI > 80
McAdam-Step	McAdam-Step 3
Beam angle	116 °
Amount of light sources / fittings	1 Qty

Outer diameter	1200 mm
Height	100 mm
Colour rendering	CRI > 80
Material	Aluminium / Steel / Plastic
Voltage	230V AC 50Hz
Lamp	LED
Light output	Direct
Shipping	Incl. converter for connection to the 230-V mains voltage
Pendulum length max.	5,000 mm
Degree of protection	IP40
Protection class	I
Voltage type	AC