




LED-Einbaudownlight, DALI dimmbar

Artikel-Nr. 12552183



LED-Einbaudownlight, DALI dimmbar, black, round. In a compact design, for installation in tool-less rapid assembly systems
 Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic / Steel, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 25W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.877lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 74°, Adjustability: Not adjustable, With control gear: Yes, Control: DALI.

Artikel-Nr.	12552183
Stand:	26.10.2021 00:04

Colour temperature	3000 K
Colour	Black
Beam angle	74 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic / Steel
Power	25 W
Lamp	LED
scope of delivery	inkl. Konverter zum Anschluss an 230 V-Netzspannung, DALI dimmbar
Colour rendering	CRI > 90

Glare evaluation	UGR < 22
Control	DALI
Outer diameter	204 mm
Built-in diameter	190 mm
Installation depth	102 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Not adjustable
Circuit type	Parallel conduction