



LED recessed spot, IP65  
Artikel-Nr. 12355083



LED recessed spot, IP65, black, square. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Silicone rubber / Plastic, Degree of protection: according to DIN EN 60529 IP65, Protection class: (EN 61140) III, Current: 350 mA, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 650lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

|             |                  |
|-------------|------------------|
| Artikel-Nr. | 12355083         |
| Stand:      | 25.10.2021 23:45 |

|                                    |                                               |
|------------------------------------|-----------------------------------------------|
| Colour temperature                 | 3000 K                                        |
| Colour                             | Black                                         |
| Length                             | 82 mm                                         |
| Beam angle                         | 38 °                                          |
| Amount of light sources / fittings | 1 Qty                                         |
| Material                           | Aluminium / Steel / Silicone rubber / Plastic |
| Lamp holder                        | Plug&Play                                     |
| Power                              | 6 W                                           |
| Lamp                               | LED                                           |
| Colour rendering                   | CRI > 80                                      |

|                      |                             |
|----------------------|-----------------------------|
| Control              | Dimming depending on driver |
| Built-in diameter    | 68 mm                       |
| Installation depth   | 50 mm                       |
| Current              | 350 mA                      |
| Degree of protection | IP65                        |
| Protection class     | III                         |
| Adjustability        | Pivoted                     |
| Length               | 82 mm                       |
| Width                | 82 mm                       |
| Swivel angle         | 30 °                        |
| Circuit type         | Series conduction           |