




LED recessed spot INDIWO83, pivoted, dim2warm
Artikel-Nr. 12476173



LED recessed spot INDIWO83, pivoted, dim2warm, white, round. In a compact design, for installation in tool-less rapid assembly systems. If the lamp is dimmed, the color temperature is reduced. Recessed spot suitable for direct mounting on normally flammable building materials. Thermal insulation allowed. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 400lm, Colour temperature: from 1.800 K up to 3.000 K, Beam angle: 36°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12476173
Stand:	25.10.2021 20:55

Colour temperature	3000 K - 1800 K
Colour	White
Beam angle	36 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Steel / Plastic
Lamp holder	Plug&Play
Power	6 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver

Outer diameter	95 mm
Built-in diameter	83 mm
Installation depth	38 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Pivoted
Swivel angle	25 °
Circuit type	Series conduction