




LED recessed spot set, phase dimmable
Artikel-Nr. 39142073



LED recessed spot set, phase dimmable, square. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, trailing-edge phase dimmable, dimensions of converter: L 110 x W 50 x H 19 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Cast iron / Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 680lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, Control: Trailing-edge phase.

Artikel-Nr.	39142073
Stand:	25.10.2021 23:22

Colour temperature	3000 K
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Cast iron / Aluminium / Glass / Plastic
Lamp	LED
Colour rendering	CRI > 80
Control	Trailing-edge phase
Outer diameter	88 mm

Built-in diameter	68 mm
Installation depth	55 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Circlip	Without circlip
Adjustability	Pivoted
Swivel angle	25 °
Circuit type	Parallel conduction