



BIRO Circle surface luminaire 450

Artikel-Nr. 13685174



| Ø (m) | E0(0°) [lx] |
|-------|---------------|
| 1.0 m | 3.213.0 811.9 |
| 2.0 m | 6.416.0 203.0 |
| 3.0 m | 9.618.9 90.2 |
| 4.0 m | 12.811.9 50.7 |
| 5.0 m | 16.014.9 32.5 |

BIRO Circle surface luminaire 450, white, round. Surface mounting, Ceiling-mounted. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP40, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 25W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.550lm, Light colour : White, Beam angle: 120°, With control gear: Yes. This luminaire contains incorporated and non-exchangeable LED light sources

| | |
|--------------------|------------------|
| Artikel-Nr. | 13685174 |
| Stand: | 18.06.2021 14:42 |

| | |
|----------------------------------|---------------|
| Type of dimming | on/off |
| Colour | White |
| Colour of light | 4000 K |
| System efficiency | 102 lm/W |
| Luminous flux | 2,550 lm |
| Material cover | Plastic, opal |
| Rated life time L80/B50 at 25 °C | 50000 h |
| Rated life time L70/B50 at 25 °C | 50000 h |
| System output | 25 W |
| Colour rendering | CRI > 80 |
| McAdam-Step | McAdam-Step 3 |
| Beam angle | 120 ° |

| | |
|------------------------------------|---|
| Amount of light sources / fittings | 1 Qty |
| Outer diameter | 450 mm |
| Height | 100 mm |
| Colour rendering | CRI > 80 |
| Material | Aluminium / Steel / Plastic |
| Voltage | 230V AC 50Hz |
| Lamp | LED |
| Light output | Direct |
| Shipping | Incl. converter for connection to the 230-V mains voltage |
| Degree of protection | IP40 |
| Protection class | I |
| Voltage type | AC |