




BIRO Circle surface luminaire 1.200  
Artikel-Nr. 13683174



BIRO Circle surface luminaire 1.200, white, round. Surface mounting, Ceiling-mounted Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP40, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 175W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 20.475lm, Colour temperature: 4000 K, Light colour : White, Beam angle: 116°, With control gear: Yes. This luminaire contains incorporated and non-exchangeable LED light sources

|             |                  |
|-------------|------------------|
| Artikel-Nr. | 13683174         |
| Stand:      | 21.07.2021 20:03 |

|                                  |               |
|----------------------------------|---------------|
| control                          | on/off        |
| Colour                           | White         |
| Colour of light                  | 4000 K        |
| System efficiency                | 117 lm/W      |
| Luminous flux                    | 20,475 lm     |
| Material cover                   | Plastic, opal |
| Rated life time L80/B50 at 25 °C | 50000 h       |
| Rated life time L70/B50 at 25 °C | 50000 h       |
| System output                    | 175 W         |
| Colour rendering                 | CRI > 80      |
| McAdam-Step                      | McAdam-Step 3 |
| Beam angle                       | 116 °         |

|                                    |                                                           |
|------------------------------------|-----------------------------------------------------------|
| Amount of light sources / fittings | 1 Qty                                                     |
| Outer diameter                     | 1200 mm                                                   |
| Height                             | 100 mm                                                    |
| Colour rendering                   | CRI > 80                                                  |
| Material                           | Aluminium / Steel / Plastic                               |
| Voltage                            | 230V AC 50Hz                                              |
| Lamp                               | LED                                                       |
| Light output                       | Direct                                                    |
| Shipping                           | Incl. converter for connection to the 230-V mains voltage |
| Degree of protection               | IP40                                                      |
| Protection class                   | I                                                         |
| Voltage type                       | AC                                                        |