





BIRO Square surface mounted luminaire
Artikel-Nr. 13710174



BIRO Square surface mounted luminaire, white, square. Surface mounting, Ceiling-mounted Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP40, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 44W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 5.456lm, Colour temperature: 4000 K, Light colour : White, Beam angle: 114°, With control gear: Yes. This luminaire contains incorporated and non-exchangeable LED light sources

Artikel-Nr.	13710174
Stand:	21.07.2021 19:51

control	DALI
Colour	White
Colour of light	4000 K
System efficiency	124 lm/W
Luminous flux	5,456 lm
Material cover	Plastic, opal
System output	44 W
Colour rendering	CRI > 80
Beam angle	114 °
Amount of light sources / fittings	1 Qty
Width	600 mm

Height	100 mm
Colour rendering	CRI > 80
Material	Aluminium / Steel / Plastic
Voltage	230V AC 50Hz
Lamp	LED
Light output	Direct
Shipping	Incl. converter for connection to the 230-V mains voltage
Degree of protection	IP40
Protection class	I
Voltage type	AC