





LED recessed spot INDIWO68, pivoted
Artikel-Nr. 12295643



LED recessed spot INDIWO68, pivoted, titanium, square. In a compact design, for installation in tool-less rapid assembly systems. Recessed spotlight suitable for direct mounting on normally flammable building materials. Thermal insulation allowed. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 540lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 36°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12295643
Stand:	25.10.2021 21:49

Colour temperature	3000 K
Colour	Titanium
Beam angle	36 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Steel / Plastic
Lamp holder	Plug&Play
Power	6 W
Lamp	LED
Colour rendering	CRI > 80

Control	Dimming depending on driver
Built-in diameter	68 mm
Installation depth	45 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Pivoted
Swivel angle	15 °
Circuit type	Series conduction