




LED recessed spot, IP65
Artikel-Nr. 12353253



LED recessed spot, IP65, alu, round. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Silicone rubber / Plastic, Degree of protection: according to DIN EN 60529 IP65, Protection class: (EN 61140) III, Current: 350 mA, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 650lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12353253
Stand:	25.10.2021 22:40

Colour temperature	3000 K	Control	Dimming depending on driver
Colour	Alu	Outer diameter	82 mm
Beam angle	38 °	Built-in diameter	68 mm
Amount of light sources / fittings	1 Qty	Installation depth	50 mm
Material	Aluminium / Steel / Silicone rubber / Plastic	Current	350 mA
Lamp holder	Plug&Play	Degree of protection	IP65
Power	6 W	Protection class	III
Lamp	LED	Adjustability	Pivoted
Colour rendering	CRI > 80	Swivel angle	30 °
		Circuit type	Series conduction