




LED recessed spotlight CORE
Artikel-Nr. 88677185



LED recessed spotlight CORE, black, round. In a compact design, for installation in tool-less rapid assembly systems. Including a light source: 1 x LED COB, power of LED: 44 W, system power: 48.9 W, heat dissipation: passive (without a fan), material: aluminum / glass, rotation angle: can be rotated/swiveled, dimensions of lamp: Ø 205 mm x 200 mm, weight: 1.7 kg, including an driver, on/off switchable (dimensions: L 125 x W 68 x H 32 mm), power factor > 0.9 (230 V AC 50 Hz). Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 48.9W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 4.661lm, Colour temperature: 3.500 K, Light colour : White, Beam angle: 38°, Adjustability: Rotable and pivoted, With control gear: Yes, Control: on/off.

Artikel-Nr.	88677185
Stand:	26.10.2021 00:25

Beam angle	38 °
Colour temperature	3500 K
Colour	schwarz
Luminous flux	4,661 lm
System efficiency	95 lm/W
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass / Plastic
Power	48,9 W
Lamp	LED
Colour rendering	CRI > 80

Control	on/off
Outer diameter	205 mm
Built-in diameter	190 mm
Installation depth	180 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Rotable and pivoted
Rotation angle	350 °
Swivel angle	45 °
Circuit type	Parallel conduction