




LED recessed spotlight
Artikel-Nr. 12592184



LED recessed spotlight, black, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 32W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 4.030lm, Colour temperature: 4000 K, Light colour : White, Beam angle: 30°, Adjustability: Rotable and pivoted, With control gear: Yes.

Artikel-Nr.	12592184
Stand:	20.07.2021 23:30

Colour of light	4000 K
Colour	Black
Beam angle	30 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass / Plastic
Power	32 W
Lamp	LED
Colour rendering	CRI > 90
Outer diameter	182 mm

Built-in diameter	170 mm
Installation depth	125 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Rotable and pivoted
Rotation angle	355 °
Swivel angle	30 °
Circuit type	Parallel conduction

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.