




LED recessed downlight  
**Artikel-Nr. 12551184**



LED recessed downlight, black, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic / Steel, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 32.5W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.720lm, Colour temperature: 4000 K, Light colour : White, Beam angle: 70°, Adjustability: Not adjustable, With control gear: Yes.

<b>Artikel-Nr.</b>	<b>12551184</b>
<b>Stand:</b>	19.07.2021 11:00

Colour	Black
Beam angle	70 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic / Steel
Power	32,5 W
Lamp	LED
Colour rendering	CRI > 90
Glare evaluation	UGR < 22

Outer diameter	230 mm
Built-in diameter	210 mm
Installation depth	95 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Not adjustable
Circuit type	Parallel conduction