



LED recessed spot set, on/off  
**Artikel-Nr. 38262083**



| Distance (m) | Beam Diameter (m) | Beam Area (m²) |
|--------------|-------------------|----------------|
| 1.0 m        | 0.710.6           | 1295.1         |
| 2.0 m        | 1.411.3           | 323.8          |
| 3.0 m        | 2.111.9           | 143.9          |
| 4.0 m        | 2.812.5           | 80.9           |
| 5.0 m        | 3.513.1           | 51.8           |

LED recessed spot set, on/off, white, square. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, on/off switchable, dimensions of converter: L 68 x W 35 x H 21 mm . Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6.5W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 740lm, Colour temperature: 2.700 K, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, Control: on/off.

|                    |                  |
|--------------------|------------------|
| <b>Artikel-Nr.</b> | <b>38262083</b>  |
| <b>Stand:</b>      | 26.10.2021 00:46 |

|                                    |                     |
|------------------------------------|---------------------|
| Colour temperature                 | 2700 K              |
| Colour                             | White               |
| Beam angle                         | 38 °                |
| Amount of light sources / fittings | 1 Qty               |
| Material                           | Aluminium / Plastic |
| Lamp                               | LED                 |
| Colour rendering                   | CRI > 80            |
| Control                            | on/off              |
| Built-in diameter                  | 68 mm               |

|                      |                     |
|----------------------|---------------------|
| Installation depth   | 38 mm               |
| Voltage              | 230V AC 50Hz        |
| Luminous flux        | 750 lm              |
| Degree of protection | IP20                |
| Protection class     | II                  |
| Adjustability        | Pivoted             |
| Swivel angle         | 30 °                |
| Circuit type         | Parallel conduction |