



BIRO Circle surface luminaire 1.200
Artikel-Nr. 13693164



BIRO Circle surface luminaire 1.200, silver, round. Surface mounting, Ceiling-mounted Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP40, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 175W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 20.475lm, Colour temperature: 4000 K, Light colour : White, Beam angle: 116°, With control gear: Yes. This luminaire contains incorporated and non-exchangeable LED light sources

Artikel-Nr.	13693164
Stand:	21.07.2021 20:26

control	DALI
Colour	Silver
Colour of light	4000 K
System efficiency	117 lm/W
Luminous flux	20,475 lm
Material cover	Plastic, opal
Rated life time L80/B50 at 25 °C	50000 h
Rated life time L70/B50 at 25 °C	50000 h
System output	175 W
Colour rendering	CRI > 80
McAdam-Step	McAdam-Step 3
Beam angle	116 °

Amount of light sources / fittings	1 Qty
Outer diameter	1200 mm
Height	100 mm
Colour rendering	CRI > 80
Material	Aluminium / Steel / Plastic
Voltage	230V AC 50Hz
Lamp	LED
Light output	Direct
Shipping	Incl. converter for connection to the 230-V mains voltage
Degree of protection	IP40
Protection class	I
Voltage type	AC