




LED recessed spot

**Artikel-Nr. 12395254**

LED recessed spot, alu, round. In a compact design, for installation in tool-less rapid assembly systems  
Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 12W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.280lm, Colour temperature: 4.000 K, Light colour : White, Beam angle : 38°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

|                                    |                             |                      |                   |
|------------------------------------|-----------------------------|----------------------|-------------------|
| <b>Artikel-Nr.</b>                 |                             | <b>12395254</b>      |                   |
| <b>Stand:</b>                      |                             | 26.10.2021 03:46     |                   |
|                                    |                             |                      |                   |
| Colour temperature                 | 4000 K                      | Outer diameter       | 110 mm            |
| Colour                             | Alu                         | Built-in diameter    | 95 mm             |
| Beam angle                         | 38 °                        | Installation depth   | 60 mm             |
| Amount of light sources / fittings | 1 Qty                       | Current              | 350 mA            |
| Material                           | Aluminium / Glass           | Degree of protection | IP20              |
| Lamp holder                        | Plug&Play                   | Protection class     | III               |
| Power                              | 12 W                        | Adjustability        | Pivoted           |
| Lamp                               | LED                         | Swivel angle         | 15 °              |
| Colour rendering                   | CRI > 80                    | Circuit type         | Series conduction |
| Control                            | Dimming depending on driver |                      |                   |