





LED recessed spot set, IP65, dimmable
Artikel-Nr. 39355643



LED recessed spot set, IP65, dimmable, titanium, square. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, trailing-edge phase dimmable, dimensions of converter: L 110 x W 50 x H 19 mm . Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Silicone rubber / Plastic, Degree of protection: according to DIN EN 60529 IP65, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6W, Luminous flux: 650lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, Control: Trailing-edge phase.

Artikel-Nr.	39355643
Stand:	25.10.2021 21:18

Colour temperature	3000 K
Colour	Titanium
Length	82 mm
Beam angle	38 °
Material	Aluminium / Steel / Silicone rubber / Plastic
Power	6 W
Lamp	LED
Colour rendering	CRI > 80
Control	Trailing-edge phase

Built-in diameter	68 mm
Installation depth	50 mm
Voltage	230V AC 50Hz
Degree of protection	IP65
Protection class	II
Adjustability	Pivoted
Length	82 mm
Width	82 mm
Swivel angle	30 °
Circuit type	Parallel conduction