



LED recessed spot set, on/off

**Artikel-Nr. 38364253**



Ø (m)	E0(0°) [lx]
1.0 m	0.710.6 1369.2
2.0 m	1.411.3 342.3
3.0 m	2.111.9 152.1
4.0 m	2.812.5 85.6
5.0 m	3.513.1 54.8

LED recessed spot set, on/off, alu, square. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, on/off switchable, dimensions of converter: L 68 x W 35 x H 21 mm . Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Polycarbonate, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 740lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, Control: on/off.

<b>Artikel-Nr.</b>	<b>38364253</b>
<b>Stand:</b>	26.10.2021 02:59

Colour temperature	3000 K
Colour	Alu
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Polycarbonate
Power	7 W
Lamp	LED
Colour rendering	CRI > 80
Control	on/off
Built-in diameter	68 mm

Installation depth	38 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Pivoted
Length	82 mm
Width	82 mm
Swivel angle	30 °
Circuit type	Parallel conduction