


LED recessed downlight ALTERO, IP44
Artikel-Nr. 12035753



LED recessed downlight ALTERO, IP44, white / gold, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP44*, Protection class: (EN 61140) III, Current: 500 mA, Power: 9.2W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 820lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 33°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12035753
Stand:	26.10.2021 00:02

Colour temperature	3000 K
Colour	White / Gold
Beam angle	33 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass / Plastic
Power	9,2 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver

Outer diameter	83 mm
Built-in diameter	68 mm
Installation depth	72 mm
Current	500 mA
Degree of protection	IP44 *
Protection class	III
Adjustability	Not adjustable
Circuit type	Series conduction

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.