


LED recessed downlight ALTERO, IP44  
**Artikel-Nr. 12036853**



LED recessed downlight ALTERO, IP44, black / gold, square. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP44\*, Protection class: (EN 61140) III, Current: 500 mA, Power: 9.2W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 820lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 33°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

|             |                  |
|-------------|------------------|
| Artikel-Nr. | 12036853         |
| Stand:      | 25.10.2021 20:40 |

|                                    |                             |
|------------------------------------|-----------------------------|
| Colour temperature                 | 3000 K                      |
| Colour                             | Black / Gold                |
| Length                             | 83 mm                       |
| Beam angle                         | 33 °                        |
| Amount of light sources / fittings | 1 Qty                       |
| Material                           | Aluminium / Glass / Plastic |
| Power                              | 9,2 W                       |
| Lamp                               | LED                         |
| Colour rendering                   | CRI > 80                    |
| Control                            | Dimming depending on driver |

|                      |                   |
|----------------------|-------------------|
| Built-in diameter    | 68 mm             |
| Installation depth   | 72 mm             |
| Current              | 500 mA            |
| Degree of protection | IP44 *            |
| Protection class     | III               |
| Adjustability        | Not adjustable    |
| Length               | 83 mm             |
| Width                | 83 mm             |
| Circuit type         | Series conduction |