


LED recessed spot
Artikel-Nr. 12361254



LED recessed spot, alu, round. In a compact design, for installation in tool-less rapid assembly systems Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Polycarbonate, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 770lm, Colour temperature: 4000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, control: Dimming depending on driver. This luminaire contains incorporated and non-exchangeable LED light sources

Artikel-Nr.	12361254
Stand:	20.07.2021 22:38

Colour of light	4000 K
Colour	Alu
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Polycarbonate
Lamp holder	Plug&Play
Power	7 W
Lamp	LED
Colour rendering	CRI > 80
control	Dimming depending on driver

Outer diameter	82 mm
Built-in diameter	68 mm
Installation depth	38 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Pivoted
Swivel angle	30 °
Circuit type	Series conduction