


LED recessed downlight ALTERO, IP44
Artikel-Nr. 12036854



LED recessed downlight ALTERO, IP44, black / gold, square. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP44*, Protection class: (EN 61140) III, Current: 500 mA, Power: 9.2W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 840lm, Colour temperature: 4.000 K, Light colour : White, Beam angle: 33°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12036854
Stand:	26.10.2021 02:54
Colour temperature	4000 K
Colour	Black / Gold
Beam angle	33 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass / Plastic
Power	9,2 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver
Built-in diameter	68 mm
Installation depth	72 mm
Current	500 mA
Degree of protection	IP44 *
Protection class	III
Adjustability	Not adjustable
Length	83 mm
Width	83 mm
Circuit type	Series conduction