




LED recessed spot set, phase dimmable
Artikel-Nr. 39261633



LED recessed spot set, phase dimmable, champagne, round. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, trailing-edge phase dimmable, dimensions of converter: L 110 x W 50 x H 19 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Polycarbonate, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 740lm, Colour temperature: 2.700 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, Control: Trailing-edge phase.

Artikel-Nr.	39261633
Stand:	26.10.2021 01:55

Colour temperature	2700 K
Colour	Champagne
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Polycarbonate
Power	7 W
Lamp	LED
Colour rendering	CRI > 80
Control	Trailing-edge phase

Outer diameter	82 mm
Built-in diameter	68 mm
Installation depth	38 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Pivoted
Swivel angle	30 °
Circuit type	Parallel conduction