



LED recessed spot
Artikel-Nr. 12361643



LED recessed spot, titanium, round. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Polycarbonate, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 740lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12361643
Stand:	25.10.2021 23:12
Colour temperature	3000 K
Colour	Titanium
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Polycarbonate
Lamp holder	Plug&Play
Power	7 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver
Outer diameter	82 mm
Built-in diameter	68 mm
Installation depth	38 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Pivoted
Swivel angle	30 °
Circuit type	Series conduction