





LED surface mounted panel Flat37

Artikel-Nr. 12246073



LED surface mounted panel Flat37, white, round. Surface mounting, Ceiling-mounted Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 24W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.020lm, Colour temperature: 3.000 K, Beam angle: 110°, Adjustability: Not adjustable, With control gear: Yes, Control: on/off.

Artikel-Nr.	12246073
Stand:	07.12.2021 09:46
Colour temperature	3000 K
Colour	White
Beam angle	110 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	24 W
Lamp	LED
scope of delivery	Incl. converter for connection to 230 V mains voltage and connection terminal for through wiring
Colour rendering	CRI > 80
Control	on/off
Outer diameter	245 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	I
Adjustability	Not adjustable
Aufbauhöhe	37 mm
Circuit type	Parallel conduction

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.