




LED recessed downlight QUBIC, with indirect component
Artikel-Nr. 12227173



LED recessed downlight QUBIC, with indirect component, white, square. In a compact design, for installation in tool-less rapid assembly systems. LED recessed ceiling downlight with indirect light component. Direct light flux 830 lm, indirect light flux 130 lm. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 10.5W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 960lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 40°, Adjustability: Not adjustable, With control gear: No, control: Dimming depending on driver.

Artikel-Nr.	12227173
Stand:	20.07.2021 17:45

Colour of light	3000 K
Colour	White
Length	100 mm
Beam angle	40 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Lamp holder	Plug&Play
Power	direkt 9,5 W / indirekt 1,5 W
Lamp	LED
Colour rendering	CRI > 90
control	Dimming depending on driver

Built-in diameter	68 mm
Installation depth	36 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Not adjustable
Length	100 mm
Width	100 mm
Height	23 mm
Circuit type	Series conduction