




LED surface mounted downlight IMPLEMENT, dimmable
Artikel-Nr. 12392173



LED surface mounted downlight IMPLEMENT, dimmable, white, square. Surface mounting, Ceiling-mounted. Lamp including a converter for 230-V mains voltage, trailing-edge phase. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 8.9W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 730lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 37°, Adjustability: Not adjustable, With control gear: Yes, Control: Trailing-edge phase.

Artikel-Nr.	12392173
Stand:	07.12.2021 09:44
Colour temperature	3000 K
Colour	White
Beam angle	37 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	8,9 W
Lamp	LED
scope of delivery	Incl. converter for connection to the 230-V mains voltage, dimmable
Colour rendering	CRI > 90
Control	Trailing-edge phase
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	I
Adjustability	Not adjustable
Aufbauhöhe	115 mm
Circuit type	Parallel conduction