




LED-floor recessed light HYBRIDE FLAT, V4A, IP67

Artikel-Nr. 14035223

LED-floor recessed light HYBRIDE FLAT, V4A, IP67, stainless steel, round. Recessed mounting, Floor-mounted Mounting method: Recessed mounting, Place of installation: Floor-mounted, Material: Stainless steel, Degree of protection: according to DIN EN 60529 IP67, Protection class: (EN 61140) III, Voltage: 24V, Power: 9W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 450lm, Colour temperature: 3000 K, Beam angle: 30°, With control gear: No, dimmable: No, control: on/off.

Artikel-Nr.	14035223
Stand:	25.10.2021 15:29

Colour temperature	3000 K
Colour	Stainless steel
Beam angle	30 °
Amount of light sources / fittings	1 Qty
Material	Edelstahl V4A / Aluminium / Glas
Power	9 W
Lamp	LED
scope of delivery	Including 1,000 mm connecting cable with Aquastop and ceiling mounting springs

Control	on/off
Outer diameter	130 mm
Built-in diameter	118 mm
Installation depth	35 mm
Voltage	24V
Max. load	1,000 kg
Impact resistance	IK08
Degree of protection	IP67
Protection class	III
Circuit type	Parallel conduction