




LED-floor recessed light HYBRIDE FLAT, V4A, IP67
Artikel-Nr. 14037223



LED-floor recessed light HYBRIDE FLAT, V4A, IP67, stainless steel, round. Recessed mounting, Floor-mounted Mounting method: Recessed mounting, Place of installation: Floor-mounted, Material: Stainless steel, Degree of protection: according to DIN EN 60529 IP67, Protection class: (EN 61140) III, Voltage: 24V, Power: 6W, Amount of light sources / fittings: 1 Qty, Luminous flux: 420lm, Colour temperature: 3.000 K, Beam angle: 20°, With control gear: No, dimmable: No, Control: on/off.

Artikel-Nr.	14037223
Stand:	25.10.2021 15:27

Colour temperature	3000 K	Colour rendering	CRI > 80
Colour	Stainless steel	Control	on/off
Beam angle	20 °	Outer diameter	110 mm
Amount of light sources / fittings	1 Qty	Built-in diameter	98 mm
Material	Edelstahl V4A / Aluminium / Glas	Installation depth	35 mm
Power	6 W	Voltage	24V
Lamp	LED	Max. load	1,000 kg
scope of delivery	Including 1,000 mm connecting cable with Aquastop and ceiling mounting springs	Impact resistance	IK08
		Degree of protection	IP67
		Protection class	III
		Circuit type	Parallel conduction