


QualityFlex BB-flex lighting 5 m, CRI > 80, 4,8 W / m, IP00

Artikel-Nr. 38201003



QualityFlex BB-flex lighting 5 m, CRI > 80, 4,8 W / m, IP00, white, 3.000K, CRI > 80. LED flex lighting Länge: 5000.0 mm Lampenleistung je Meter: 4.8 W/m, Lichtstrom je Meter: 490.0 lm/m, Schutzart raumseitig: IP00, Schutzklasse: III, Spannung: 24V DC, Abstrahlwinkel: 120.0 °, 60 LEDs pro Meter, Chip-Abstand (Short Pitch) : 16,7mm. Zur Individuellen Anwendung kann die LED-Flexplatine alle 100 mm eingekürzt werden. Die maximale Systemlänge von 5.000mm darf mit einer Einspeisung nicht überschritten werden. This luminaire contains incorporated and non-exchangeable LED light sources

Artikel-Nr.	38201003
Stand:	06.12.2021 18:49

Colour temperature	3000 K
Light colour	White
Luminous flux per meter	490 lm/m
Power	24 W
Rated life time L80/B20 at 25 °C	50000 h
Lamp power per meter	4.8 W/m
Beam angle	120 °
Length	5,000 mm
Width	8 mm
Aufbauhöhe	1.2 mm
Length of individual sections	100 mm
Degree of protection	IP00

Protection class	III
McAdam-Step	McAdam-Step 3
Short Pitch	16.7 mm
Number of lamps per meter	60 Qty
Voltage	24V
Voltage type	DC
Ambient temperature	-10 °C bis +40 °C
Control	Dimming depending on driver
Circuit type	Parallel conduction
Length of the connection line	300 mm
Maximum module length	5,000 mm