




LED track spotlight MINI  
**Artikel-Nr. 88393183**



LED track spotlight MINI, black, round. Surface mounting, Ceiling-mounted. Heat dissipation: passive (without fan), including driver, switchable, (230 V AC 50 Hz). Luminaire including Euro adapter for standard 3-phase tracks. Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 23W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.686lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 36°, Adjustability: Rotatable and adjustable head, With control gear: Yes, Control: on/off.

|                    |                  |
|--------------------|------------------|
| <b>Artikel-Nr.</b> | <b>88393183</b>  |
| <b>Stand:</b>      | 07.12.2021 11:51 |

|                                    |                                |
|------------------------------------|--------------------------------|
| Beam angle                         | 36 °                           |
| Colour temperature                 | 3000 K                         |
| Colour                             | strukturschwarz                |
| Luminous flux                      | 2,686 lm                       |
| Beam angle                         | 36 °                           |
| Amount of light sources / fittings | 1 Qty                          |
| Material                           | Aluminium                      |
| Power                              | 23 W                           |
| Lamp                               | LED                            |
| scope of delivery                  | inkl. Betriebsgerät, schaltbar |
| Colour rendering                   | CRI > 90                       |
| Control                            | on/off                         |

|                             |                               |
|-----------------------------|-------------------------------|
| Outer diameter              | 71 mm                         |
| Voltage                     | 230V AC 50Hz                  |
| Degree of protection        | IP20                          |
| Protection class            | I                             |
| Adjustability               | Rotatable and adjustable head |
| Length                      | 71 mm                         |
| Width                       | 71 mm                         |
| Aufbauhöhe                  | 200 mm                        |
| Rotation angle              | 350 °                         |
| Head adjustable angle       | 90 °                          |
| Circuit type                | Parallel conduction           |
| Suitable for through-wiring | No                            |