



LED surface mounted / recessed downlight MOON
Artikel-Nr. 12205073



LED surface mounted / recessed downlight MOON, white, round. Surface mounting, Ceiling-mounted. Lamp including a converter for 230-V mains voltage, trailing-edge phase. Various front rings are for color matching available in chrome 81020502, black 81020508 or nickel satin 81020515 Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 12W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.135lm, Beam angle: 110°, Adjustability: Not adjustable, With control gear: Yes, Control: Trailing-edge phase.

Artikel-Nr.	12205073
Stand:	07.12.2021 12:07

Colour temperature	3000 K / 4000 K / 6000 K
Colour	White
Beam angle	110 °
Amount of light sources / fittings	1 Qty
Control	Trailing-edge phase
Outer diameter	170 mm
Installation depth	25 mm
Colour rendering	CRI > 80
Material	Aluminium / Plastic
Aufbauhöhe	19 mm
Height-depth	19 mm
Power	12 W
Voltage	230V AC 50Hz

Lamp	LED
scope of delivery	Incl. converter for connection to the 230-V mains voltage, dimmable. Optional accessory: Front rings for modification of the housing color (magnetic attachment)
Circuit type	Parallel conduction
Degree of protection	IP20
Protection class	II
Voltage type	AC
Adjustability	Not adjustable