



Product Features

Class FA - universal connection module, shielded, insulated, for field assembly, without special tools, AWG 27-22

- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)

- shielded bushing, shield cross and cable support from zinc diecast

- cup nut and wire presorting from PA UL94 V0

- shield from German silver

- round design

- protection class: IP 67 according to IEC60529

- insulation

- quick assembly without special tools

- cable diameter 5,5 - 9,0mm

- for solid wires 0,51-0,64mm, AWG 24/1-AWG 22/1

- for stranded wires 0,46-0,78mm, AWG 27/7-AWG 22/7

- reconnectable > 4-times

- suitable for PoE++ / 4PPOE according to IEEE 802.3bt

- according to the following standards:

- ISO/IEC 11801, Cat.6A

- DIN EN 50173-1, Cat.6A

- ISO/IEC 11801, Class FA

- DIN EN 50173-1, Class FA

- ANSI/TIA/EIA-568-C.2, Category 6A

- IEEE 802.3an, 10 Gbit-Ethernet

Features

General

Surface	high-gloss
Design	jack/circular connector
shielded	Yes
Classification	Cat.7
PoweroverEthernet	Yes
Protection class IP	67
Halogen Free	Yes
Statistical goods number	85366990
Country of manufacture	CN
GTIN (EAN)	4043921661314

Dimensions/Weights without packaging	
Length mm	75
Width mm	22
Net weight piece kg	0,041
Certifications	
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,73
Packaging unit Width mm	280
Packaging unit Height mm	137
Packaging unit Depth mm	103
References	
Accessories	21207000
Similar article	13900360, 13900370

