



### Product Features

"Cat.6A iso-Patchpanel, shielded, 19"/1 U, 24 x RJ45-ports, direct mounting, light grey (similar RAL 7035)"

- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
- direct mounting
- 24 x RJ45 ports
- labelled ports (1-24)
- quick one step mounting of strain relief and shielding connection
- perfect shielding
- quick installation via LSA-contacts
- color code T568A and T568B according to TIA/EIA-568-B.2
- suitable for Cat.6 and Cat.7 cables with Ø 6-10mm
- LSA-contacts for one wire 0,4-0,63 mm Ø, AWG 26-22, maximum number of connections > 50-times
- suitable for PoE++ / 4PPoE), according to IEEE 802.3bt
- UPOE-conform
- HDBaseT conform
- according to the following standards:
  - ISO/IEC 11 801, Cat.6A, shielded
  - DIN EN 50173-1, Cat.6A, shielded
  - ANSI TIA/EIA-568-C.2, Cat.6A, shielded
  - DIN EN 60603-7-51, 500 MHz, shielded
- life > 750 cycles
- RJ11/RJ12-protected against mismatching
- GHMT certified

### Features

General	
Design	jack
shielded	Yes
Classification	Cat.6A iso
PoweroverEthernet	Yes
Protection class IP	20
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921663127
ETIM class	STANDARD
Mounting types	
(19-inch)-installation, 1 rack unit	Yes

Dimensions/Weights without packaging	
Length mm	44
Width mm	482
Height mm	114
Net weight piece kg	1,452
Certifications	
WEEE	Yes
GHMT	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	1,668
Packaging unit Width mm	510
Packaging unit Height mm	150
Packaging unit Depth mm	55
References	
Accessories	23510002, 23510003, 23510004, 23510005, 23510006, 23510007, 23611116, 23611124, 39200000, 39200002
Similar article	23610106, 23610108, 23610112, 238101100, 239101000

