



### Product Features

ClassEA iso U-Patchpanel, unshielded, 19"/1 U, 24 x RJ45-ports, for direct mounting, light grey (similar RAL 7035)

- for use in 10 Gigabit- Ethernet- Networks (transmission rate 500 MHz)
- direct mounting
- 24 x RJ45 jacks
- labelled ports (1-24)
- quick installation via LSA-contacts
- definite colouring of the LSA-contacts
- color code according to EIA/TIA 568 A and B
- suitable for Cat.6 and Cat.7 cables with Ø 6-10mm
- LSA-contacts for one wire 0,4-0,63 mm Ø, AWG 26-22, maximum number of connections > 50-times
- suitable for PoE++ / 4PPoE), according to IEEE 802.3bt
- UPOE conform
- HDBaseT conform
- according to the following standards:
  - ISO/IEC 11 801, ClassEA, unshielded
  - DIN EN 50173-1, ClassEA, unshielded
  - ANSI TIA/EIA-568-C.2, ClassEA, unshielded
- life > 750 cycles
- RJ11/12-protected for mismatching

### Features

General	
Design	jack
Classification	ClassEA iso U
PoweroverEthernet	Yes
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921662526
Mounting types	
(19-inch)-installation, 1 rack unit	Yes
Dimensions/Weights without packaging	
Length mm	44
Width mm	483
Height mm	130
Net weight piece kg	1,429

Certifications	
WEEE	Yes
GHMT	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	1,636
Packaging unit Width mm	510
Packaging unit Height mm	150
Packaging unit Depth mm	55
References	
Accessories	23510002, 23510003, 23510004, 23510005, 23510006, 23510007, 39200000, 39200002
Similar article	13700300, 234101100, 238101100

