



#### Product Features

Patch cord, 0,35m, for the connection of DIN-rail mounting devices in an electrical distribution box

- suitable für Gigabit applications (bandwith 100 MHz)
- 2 x RJ45-plugs
- S/FTP-version
- suitable for all common RJ45 data applications, respectively terminal devices
- fire behavior/Euro-class: EN13501-6:Eca
- mantle material: LSOH, FRNC
- molded bending protection
- bend radius without strain-relief > 25 mm, with strain-relief > 50 mm
- conductor: stranded copper wire, bare Ø 0,42 mm (AWG 27/7)
- according to following standards:
- DIN EN 50173-1
- ISO/IEC 11801
- suitable für PoE+ according to IEEE 802.3at

#### Features

General	
Design	plug/plug
shielded	Yes
Classification	Cat.5e
PoweroverEthernet	Yes
Halogen Free	Yes
Statistical goods number	85444210
Country of manufacture	DE
GTIN (EAN)	4043921048627
Dimensions/Weights without packaging	
Cable length mm	350
Net weight piece kg	0,019
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes

Logistics Information	
Packaging	polybag
Packaging unit Quantity	1
Packaging unit Weight kg	0,021
Packaging unit Width mm	205
Packaging unit Height mm	145
Packaging unit Depth mm	15
References	
Accessories	13910200, 23510503, 23510504, 23510505, 23810200
Similar article	21500005, 21500305, 21500405, 21500505, 21500605, 23510202

