



Product Features

Gigabit-Switch, for DIN-rail-mounting, 4 x RJ 45-ports 10/100/1000 Mbit/s, 6 x Installation-ports 10/100/1000 Mbit/s, multicast support, VLAN tagging, light grey (similar RAL 7035)

- data rates 10/100/1000 Mbit/s
- for DIN-rail mounting (144 mm)
- insulation class II
- protection class IP 20
- layer 2 - Switch
- for 10 data units
- 4 front ports (slanted outlets)
- 6 ports for permanent installation (detachable, screw terminal block, 9-pole)
- detachable, screwless 230V-plug-in terminal up to 2,5mm²
- integrated power supply: 100 V-240V AC/50-60 Hz
- power consumption: 10 VA max.
- temperature range -40°C to +45°C
- LED's for operation
- cascadable by using random front port
- autopartitioning, MDI/MDIX
- autonegotiation
- autosensing
- multicats support

Features

General

Protection class IP	20
Statistical goods number	85415900
Country of manufacture	DE
GTIN (EAN)	4043921663479
ETIM class	STANDARD

Mounting types

DIN-Rail	Yes
----------	-----

Dimensions/Weights without packaging

Length mm	90
Width mm	143
Height mm	67
Net weight piece kg	0,289

Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	0,454
Packaging unit Width mm	185
Packaging unit Height mm	145
Packaging unit Depth mm	95
References	
Accessories	13910200, 23510201, 23510202, 23810200
Similar article	23510503, 23510504

