



Product Features

- ClassEA iso U-jack, unshielded, single, surface mounting, pure white (similar RAL 9010)
- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
 - quick installation via LSA-contacts
 - RJ45-openings slanted downwards
 - colour code T568A and T568B according to TIA / EIA-568-B.2
 - suitable for Cat.6 and Cat.7 cables (Ø 6-10 mm)
 - LSA-contacts for one wire 0,4-0,63 mm Ø, AWG 26-22, maximum number of connections > 50-times
 - suitable for PoE++ / 4PPoE according to IEEE 802.3bt
 - UPOE conform
 - HDBaseT conform
 - according to the following standards:
 - ISO/IEC 11 801, ClassEA, unshielded
 - DIN EN 50173-1, ClassEA, unshielded
 - ANSI TIA/EIA-568-C.2, ClassEA
 - life > 750 cycles
 - RJ11/12 protected against mismatching

Features

General	
Design	jack
Classification	ClassEA iso U
PoweroverEthernet	Yes
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921661918
Mounting types	
DIN-Rail	Yes
surface-mounted	Yes
Dimensions/Weights without packaging	
Length mm	65
Width mm	80
Height mm	26
Net weight piece kg	0,032

Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,42
Packaging unit Width mm	141
Packaging unit Height mm	165
Packaging unit Depth mm	72
References	
Accessories	10010070, 13510505, 13510512, 13510513, 13510514, 13510515, 13510516, 39200000, 39200002
Similar article	132115030, 13700300

