



Product Features

TAE-jack, NFN, surface mounting, for 1 telephone and 2 ancillary equipment, 3x6 way, 6 screw terminals, pure white (similar RAL 9010)

- contacts made of German silver, respectively brass, tin-plated.

- gold plated contacts

- voltage: 125 V DC/AC

- circuit load: max. 10 VA

- isolation withstand: > 200 MOhm

- contact withstand: < 20/30 mOhm

- voltage withstand: 1000 V, 50 Hz, 1 Min.

- life (insertions and withdrawals): > 10.000 cycles

- metric screws for center plates

- suitable for the design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)

Features

General

Surface	high-gloss
Design	jack
Protection class IP	20
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921036402
ETIM class	STANDARD

Mounting types

DIN-Rail	Yes
surface-mounted	Yes

Dimensions/Weights without packaging

Length mm	65
Width mm	80
Height mm	27
Net weight piece kg	0,031

Certifications

WEEE	Yes
CE	Yes
RoHS conform	Yes

Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,409
Packaging unit Width mm	141
Packaging unit Height mm	165
Packaging unit Depth mm	72
References	
Accessories	10010070
Similar article	10210204, 10210517, 10310114

