



Product Features

TAE-jack, NFF, flush mounting, for 2 telephones and 1 ancillary equipment, 3x6 way, 2x6 screw terminals, with spreading claws, suitable for the design wall plates of all well-known manufacturer, pure white (similar RAL 9010)

- metal mounting ring
- with spreading claws
- contacts made of German silver, respectively brass, tin-plated.
- gold plated contacts
- voltage: 125 V DC/AC
- circuit load: max. 10 VA
- isolation withstand: > 200 MOhm
- contact withstand: < 20/30 mOhm
- voltage withstand: 1000 V, 50 Hz, 1 Min.
- life (insertions and withdrawals): >10.000 cycles
- metric screws for center plates
- suitable for the design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)

Features

General	
Surface	high-gloss
Support ring	Yes
Design	jack
Design capability	Yes
Protection class IP	20
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921037331
ETIM class	STANDARD
Mounting types	
floor outlet box/underfloor installation	Yes
flush-mounted	Yes
trunking installation	Yes
Dimensions/Weights without packaging	
Length mm	70
Width mm	70
Height mm	29
Net weight piece kg	0,044

Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,54
Packaging unit Width mm	141
Packaging unit Height mm	165
Packaging unit Depth mm	72
References	
Accessories	10010051, 10010055, 13511503, 13910053
Similar article	10210517, 10310114, 10310222

