



Product Features

UAE-jack, single, flush mounting, 8 way, 8 screw terminals, with spreading claws, pure white (similar RAL 9010)

- openings for 6- and 8-way plugs (RJ12 and RJ45)
- suitable for RJ11/12 without additional reducing adapters
- metal mounting ring
- with spreading claws
- jacks positioned downward sloped
- screw terminals for wires up to 1mm Ø, 2 wires at each contact
- alternative LSA-terminals for one wire 0,4-0,63 mm Ø, AW 26-22, max. number of connections > 50-times
- gold plated contacts
- voltage: 125 V
- operation current: 1 A bei 50° C
- voltage withstand: 1000 V, 50 Hz, 1 Min.
- contact withstand: < 20 mOhm
- according to the following standards:
- TIA/EIA-568-B.2-2001, Cat. 3
- life (insertions and withdrawals): > 2500 cycles
- suitable for the design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)

Features

General	
Cover plate	Yes
Centre plate	Yes
Support ring	Yes
Design	jack
Design capability	Yes
Classification	Cat.3
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921039991
ETIM class	STANDARD
Mounting types	
floor outlet box/underfloor installation	Yes
flush-mounted	Yes
trunking installation	Yes

Dimensions/Weights without packaging	
Length mm	80
Width mm	80
Height mm	31
Net weight piece kg	0,049
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,59
Packaging unit Width mm	138
Packaging unit Height mm	166
Packaging unit Depth mm	83
References	
Accessories	10010055, 13511503, 681072
Similar article	13010129, 13010407



8 Kontakte

