



Product Features

UAE-jack, double, surface mounting, with LSA-contacts, 2 x 8 way, 2 x 8 LSA contacts, pure white (similar RAL 9010), with LSA-contacts

- openings for 6- and 8-way plugs (RJ12 and RJ45)
- suitable for RJ11/12 without additional reducing adapters
- jacks positioned downward sloped
- screw terminals for wires up to 1mm Ø, 2 wires at each contact
- LSA-terminals for one wire 0,4-0,63 mm Ø, AW 26-22, max. number of connections > 50-times
- gold plated contacts
- resistance switchable via jumper
- voltage: 125 V
- operation current: 1 A bei 50° C
- voltage withstand: 1000 V, 50 Hz, 1 Min.
- contact withstand: < 20 mOhm
- according to the following standards:
- TIA/EIA-568-B.2-2001, Cat. 3
- life (insertions and withdrawals): > 2500 cycles
- suitable for the design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)

Features

General	
Design	jack
Classification	Cat.3
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921061657
ETIM class	STANDARD
Mounting types	
DIN-Rail	Yes
surface-mounted	Yes
Dimensions/Weights without packaging	
Length mm	65
Width mm	80
Height mm	26
Net weight piece kg	0,036

Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,44
Packaging unit Width mm	134
Packaging unit Height mm	134
Packaging unit Depth mm	82
References	
Accessories	10010070, 681072
Similar article	13010131, 13011216

