



Product Features

Cat.6A iso U-jack, unshielded, single, flush mounting, with plastic mounting brackets, with spreading claws, suitable for the design wall plates of all well-known manufacturer

- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
- quick installation via LSA-contacts
- RJ45-openings slanted downwards
- with plastic mounting brackets
- with spreading claws
- colour code T568A and T568B according to TIA / EIA-568-B.2
- suitable for Cat.6 and Cat.7 cables (Ø 6-10 mm)
- LSA-contacts for one wire 0,4-0,63 mm Ø, AWG 26-22, maximum number of connections > 50-times
- suitable for PoE++ / 4PPoE according to IEEE 802.3bt
- UPOE conform
- HDBaseT conform
- suitable for the UAE-design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)
- according to the following standards:
 - ISO/IEC 11 801, Cat.6A, unshielded
 - DIN EN 50173-1, Cat.6A, unshielded
 - ANSI TIA/EIA-568-C.2, Cat.6A
 - life > 750 cycles
 - RJ11/12 protected against mismatching

Features

General	
Design	jack
Design capability	Yes
Classification	Cat.6A iso U
PoweroverEthernet	Yes
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921059616
ETIM class	STANDARD
Mounting types	
floor outlet box/underfloor installation	Yes
flush-mounted	Yes
trunking installation	Yes

Dimensions/Weights without packaging	
Length mm	70
Width mm	50
Height mm	29
Net weight piece kg	0,024
Certifications	
WEEE	Yes
CE	Yes
RoHS conform	Yes
Logistics Information	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,34
Packaging unit Width mm	141
Packaging unit Height mm	165
Packaging unit Depth mm	72
References	
Accessories	10000041, 10000042, 10000061, 10000062, 10010001, 10010051, 10010055, 10010056, 13500042, 13500062, 13510002, 13510052, 13510505, 13510512, 13510513, 13510514, 13510515, 13510516, 39200000, 39200002
Similar article	13411201, 13411501, 136104030, 13700300

