



#### Product Features

- Cat.6A iso U-jack, unshielded, single, flush mounting, with plastic mounting brackets, with spreading claws, pure white (similar RAL 9010)
- for use in 10 Gigabit-Ethernet-Networks (transmission bandwidth 500 MHz)
- quick installation via LSA-contacts
- RJ45-openings slanted downwards
- with plastic mounting brackets
- with spreading claws
- colour code T568A and T568B according to TIA / EIA-568-B.2
- suitable for Cat.6 and Cat.7 cables (Ø 6-10 mm)
- LSA-contacts for one wire 0,4-0,63 mm Ø, AWG 26-22, maximum number of connections > 50-times
- suitable for PoE++ / 4PPoE according to IEEE 802.3bt
- UPOE conform
- HDBaseT conform
- suitable for the UAE-design wall plates of all well-known manufacturer (Berker, Busch-Jäger, GIRA, JUNG, Merten etc.)
- according to the following standards:
  - ISO/IEC 11 801, Cat.6A, unshielded
  - DIN EN 50173-1, Cat.6A, unshielded
  - ANSI TIA/EIA-568-C.2, Cat.6A
- life > 750 cycles
- RJ11/12 protected against mismatching

#### Features

General	
Cover plate	Yes
Centre plate	Yes
Design	jack
Design capability	Yes
Labeling field	Yes
Classification	Cat.6A iso U
PoweroverEthernet	Yes
Halogen Free	Yes
Statistical goods number	85369010
Country of manufacture	DE
GTIN (EAN)	4043921059623
ETIM class	STANDARD
Mounting types	
floor outlet box/underfloor installation	Yes
flush-mounted	Yes

trunking installation	Yes
<b>Dimensions/Weights without packaging</b>	
Length mm	80
Width mm	80
Height mm	31
Net weight piece kg	0,039
<b>Certifications</b>	
WEEE	Yes
CE	Yes
RoHS conform	Yes
<b>Logistics Information</b>	
Packaging	box
Packaging unit Quantity	10
Packaging unit Weight kg	0,5
Packaging unit Width mm	144
Packaging unit Height mm	165
Packaging unit Depth mm	83
<b>References</b>	
Accessories	10010001, 10010051, 10010055, 13510002, 13510052, 13510505, 13510512, 13510513, 13510514, 13510515, 13510516, 39200000, 39200002
Similar article	13410401, 13411501, 136112030, 13700300



8 Kontakte

