
THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.




0.220±0.015

(5.59±0.38)

В

0.060±0.010 _ (1.52±.25)



REF 0.40 - (10.2)	 0.26
	*

PANDUIT PART NUMBER	COLOR	USE WITH THESE CABLE TIE ** CROSS-SECTIONS	WEIGHT LBS/100 pcs.	
EMS-A	NATURAL	M,I,S	0.55 (250)	
EMS-A-O	WEATHER RESISTANT BLACK	M,I,S	0.55 (250)	

NOTES:

- 1. DESIGNED FOR USE WITH EPOXY ADHESIUVE (ADHESIVE NOT INCLUDED WITH EMS-A)
- 2. MOUNTING INSTRUCTIONS: (A) APPLY ADHESIVE TO PART. (B) APPLY SUFFICIENT PRESSURE TO FORCE ADHESIVE INTO GROOVES.

 (C) ALLOW ADHESIVE TO CURE BEFORE APPLYING
 - LOAD TO MOUNT.

 B

- *3. FOR PACKAGE SIZE SEE PART NUMBER SUFFIX DESIGNATION ON CURRENT PRICE SHEET.
- *4. CABLE TIE CROSS-SECTION CODE: M=MINIATURE, I=INTERMEDIATE, S=STANDARD.
- 5. BAG MAY CONTAIN EXTRA PIECES TO COMPENSATE FOR VARIANCE IN THE PACKAGING PROCESS. PANDUIT ASSURES MINIMUM PIECE COUNT AS STATED ON THE BAG.

								TITLE	
								EMS-A	
A								EPOXY MOUNT, STANDARD	
								CUSTOMER DRAWING	
								G03597FH/03 DATASET FILE NAME	
	03	1/18/2021	RVU	JADE	RMHI	ADDED NOTE 5.	GAECN05860	G03597FH_DC_GB0239HZ/03D	
	02C	2/28/18	RVU	DJW	JHAC	CHANGE FROM .057 +/005 TO .060 +/010 [1.52 +/-0.25].	GAECN04510	UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]	
	01B	12/15/09	GDH			DIM 0.220 ± 0.015 WAS: 0.210 ± 0.015, DIM 0.057 ± 0.015 WAS .065+0.015/-0.010	GB0239HZ	.x ± 0.05 [1.3] .xxx ± 0.010 [0.25] NYLON 6/6	
JA/20	01A	3/20/09	TMSA			REVISED DRAWING TO TEAMCENTER NAMING CONVENTION AND ADDED MASTER MODEL TO DRAWING	GB0239HZ	THIRD ANGLE PROJECTION GB0239HZ	
D10100	REV	DATE	BY	СНК	APR	DESCRIPTION	ECN	TMSA 3/20/09 JHAC 1:1 SHT 1 OF 1	
							_		