


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



NOTES:

1. MAT'L. - NEOPRENE:
RATING AS REQUIRED TO MEET MIL-R-6855 SPEC.
2. COLOR - BLACK
- Ⓐ 3. PART WEIGHT: 8.7 LBS, PER 100 FT.
4. 60±5 SHORE A DUROMETER RATING
5. TEMPERATURE RANGE OF -40° F (-40° C) TO 200° F (93° C)
6. DIM'S IN [BRACKETS] ARE MILLIMETERS.

REV	DATE	BY	CHK	APR	DESCRIPTION	ECN
02A	4/13	JAMB	MIM	RGRO	UPDAE DRAWING TO NEW GLOBAL PANDUIT TITLE BLOCK WITH PANDUIT LOGO	SSECN01049
01A	6/05	JAMB	EJD	SKB	Ⓐ REMOVED PART WGT "43.5 lbs PER 500 FT"	12683
00A	5/05	JMMR	EJD	SKB	DRAWING RELEASED	12198

TITLE MLTEH/SH CUSHION SLEEVING PCSSH-B-CR					
CUSTOMER DRAWING					
ITEM REVISION NAME N41202BS/02			PANDUIT		
DATASET FILE NAME N41202BS_DC/02A					
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm]					
.x ± .1 [2.54]		.xxx ± .005 [.127]			
.xx ± .01 [.25]		ANGLES ± 5 °			
			THIRD ANGLE PROJECTION		
DRAWN BY JMMR			DATE 5/05		CHK EJD
SCALE 3:1			DRAWING NUMBER: N41202BS_DC		SIZE A
SHT 1 OF 1					